

EXAN Windows Based Terminals

EXAN's Window Based Terminals WBT product range is the latest high-end technology solution for the global WBT market. With a product portfolio from Entry Level stand alone WBT to an Integrated WBT with a Touch Screen inside the LCD display, we have the products that the market and customer wants.

EXAN is a WBT for today's environment that provides the highest degree of Total Cost of Ownership (TCO), Return On Investment (ROI) and energy saving.

EXAN WBT's are powerful and cost effective and can connect to Microsoft dot Net Server, Microsoft Windows 2000, Windows NT and also Citrix Meta Frame and Win Frame Operating Systems.

EXAN WBT's delivers all Windows applications and also Text Terminal Emulation, which can easily connect to hosts such as IBM AS/400, IBM Mainframes, UNIX, VMS/VAX, Data General etc.

With the included full TCOSoft Remote Management software package the EXAN WBT range gives the Administrator the added benefits of centrally controlling all the EXAN WBT's on the Network. Some of the features that the Administrator can do are: Add New Devices, Load Device Lists, Retrieve and Update the Terminal Properties, Schedule the Devices for Image Updating, Change Management Password on WBT's etc.

Our manufacturing plants are all ISO 9000 and ISO 140000 certified.

KEY FEATURES

- CE. Net and xp Operating Systems
- Microsoft RDP 5.1 Protocol
- Citrix ICA 6.30 Protocol
- Fast 10/100Mbit Ethernet
- Terminal Emulators
- Multiple Session support
- Embedded Local Browsers
- USB, Serial, Parallel ports
- Touch screen support
- Wireless LAN built in
- No moving parts

BENEFITS

- Industry standard Software
- Very easy to Install and Configure
- Flexible Operation
- High Performance
- Local Printing support
- Free Administration Package
- Low Total Cost of Ownership (TCO)
- High Return On Investment (ROI)
- Totally silent

At EXAN we have two decades of experience, technical expertise and market knowledge in manufacturing CRT tubes, LCD Panels, Monitors and other IT products to the distribution and OEM market. We are a partner that can strengthen your position and competitive edge over your competition with the products that the market requires today.



EXAN Technology Limited
Unit 55, 3 Courthill House
60 Water Lane
Wilmslow
Cheshire
SK9 5AJ
ENGLAND

TEL: +44 (0)1625 25 24 18
FAX: +44 (0)1625 25 14 47
Email: info@exantech.com
Website: www.exantech.com



Windows Based Terminals, Thin Servers and Wireless LAN's



www.exantech.com



EX2220



EX3331xp



EX3331W



EX7331 EX7331T



MODEL:	EX2220	EX3311	EX3331	EX3331B	EX3331W	EX3331xp	EX7331	EX7331T
PROCESSOR:	•	•	•	•	•	•	•	•
								SIS 550, 200 MHz Processor NS GXI, 200 MHz Processor NS GXI, 300 MHz Processor
COMMUNICATION:	•	•	•	•	•	•	•	•
								Microsoft RDP 5.1 Citrix ICA 6.30-1061 Local Mini Browser Microsoft Internet Explorer 5.5 Browser Microsoft Internet Explorer 6.0 TCP/IP with DNS and DHCP SNMP Support Wireless LAN PCMCII IEEE 802.11b 128-bit Encryption option for RDP and ICA Protocols
EMBEDDED O.S.:	•	•	•	•	•	•	•	•
								Microsoft CE.Net Microsoft xp
DISPLAY RES.:	•	•	•	•	•	•	•	•
								640x480, 800x600, 1024x768, with 256/ High colours* 640x480, 800x600, 1024x768, 1280x1024 with 256/ High colours* Flicker free up to 85 Hz 1024x768 @60 Hz with 256/High colours* Built in to a 15" TFT LCD monitor ELO Touch and Micro Touch support Built in ELO Touch Screen Panel
MEMORY:	•	•	•	•	•	•	•	•
								SDRAM-64MB Standard, expandable to 256MB SDRAM-256MB Standard Flash memory - DOC 8MB, expandable to 96MB Flash memory - DOC 16MB, expandable to 96MB Flash memory - DOM 256MB Video RAM 4MB Video RAM 8MB
SERVER OPERATING SYSTEM SUPPORT:	•	•	•	•	•	•	•	•
								Microsoft dot Net Server Microsoft Windows 2000 (Server Edition) Microsoft Windows NT4.0 (TSE) Citrix Win Frame Citrix Meta Frame
TEXT TERMINAL EMULATION:	•	•	•	•	•	•	•	•
								ERICOM Power Term IBM - TN3270, TN5250 Printer and Display Digital - VT52/100/220/320/420/520/525 BBS ANSI, SCO ANSI, AT386 Vyse 50/60, DG D210, D211, D212, D410, D411, D412, Televideo TVI 925, TVI 950 AIXTERM, SIEMENS, TANDHEM 6530, HP 700/92, HP 700/96
ENVIRONMENT:	•	•	•	•	•	•	•	•
								Operating Temperature: 5 C to 40 C (41F to 104F) Storage Temperature: -40 C to 60 C (-4F to 140F) Relative Humidity: 90% maximum, non condensing Operating Altitude Range: 1 to 10,000 feet (0-3050m)

All details correct at time of going to press. Specifications may change without notice.

MODEL:	EX2220	EX3311	EX3331	EX3331B	EX3331W	EX3331xp	EX7331	EX7331T
AUDIO:	•	•	•	•	•	•	•	•
								Microphone IN (Mono) Line out, 1/8 inch mini connector 16-bit Stereo Sound 44.1 kHz Sample Rate Internal mini Speaker in unit Internal Speakers in Stand / Base of the unit
INPUT / OUTPUT:	•	•	•	•	•	•	•	•
								VGA-type Video Output 10/100 dual speed Ethernet, Twisted Pair (RJ45) One Parallel port (DB-25 female connector) One Serial port RS232 (DB-9 male connector) Two Serial port RS232 (DB-9 male connector) Enhanced PS/2 Mouse Interface Enhanced PS/2 Keyboard Interface Two USB Ports
INTERNATIONAL KEYBOARD SUPPORT:	•	•	•	•	•	•	•	•
								USA, UK, German, French, Brazil, Italian, Dutch, Swedish, Portuguese, Spanish, Denmark, Norway, Finland, Iceland, Belgium, Austria, Switzerland, Greece, Turkey, Israel, Russia, Latin America
REMOTE MANAGEMENT:	•	•	•	•	•	•	•	•
								TCO Soft Remote Director FTP Firmware Update
POWER:	•	•	•	•	•	•	•	•
								No moving parts Full range auto-sensing 100-240VAC @ 47Hz-63Hz 10 Watts 15 Watts 35 Watts External Power supply via umbilical cable Built in Power supply for WBT and LCD Monitor
REGULATORY COMPLIANCE:	•	•	•	•	•	•	•	•
								C-UL, TUV, FCC Class B, CE Mark
DIMENSIONS:	•	•	•	•	•	•	•	•
								194 x 151 x 40 mm (WxDxH) 231 x 201 x 45 mm (WxDxH) 396 x 172 x 377 mm (WxDxH)
WEIGHT:	•	•	•	•	•	•	•	•
								0.65 kg 1.35 kg 5.10 kg



* High colour available when using Citrix ICA Protocol
** The housing for the models EX3311, EX3331, EX3331B EX3331W and EX3331xp are identical

Windows and Windows NT are registered trademarks of Microsoft Corp. ICA is a registered trademark of Citrix Systems, Inc. Pentium is a trademark of Intel Corp. Cyrix is a registered trademark of Cyrix Corp. Media GXI is a trademark of Cyrix Corp. The energy Star logo does not represent endorsement of any product or service. All other products are trademarks and/or registered trademarks of their respective companies.